

EPSON 9000 Dye based inks

Full color reproduction suitable for indoor use. Maximum print width is 43". Note- please see current finishing size limitations. Imaging on the 9000 is done via PostScript thus suitable for imaging from supportive applications such as QuarkXpress. Output resolution is 720dpi using Piexo technology.

EPSON 9600 Ultra chrome inks

Full color reproduction suitable for indoor or outdoor (if laminated or waterproof coating is applied) use. Maximum print width is 43". Note- please see current finishing size limitations. The 9600 is a nonpostscript device. This printing choice should not be selected for documents with placed eps elements. It does work well with non postscript vector graphics and especially bitmap images. Any document containing postscript elements should be provided for output as a PDF file format document. See PDF file information below.

Application and platform information: Applicaton(program): _____ Version: _____ Platform (Mac/PC) _____

Color mode used: CMYK RGB (must all be of the same color mode)

Name of document to be printed: # of pages within doc. # of prints of each page Enlargement/Reduction Final print size Total # of prints

Name of document to be printed:	# of pages within doc.	# of prints of each page	Enlargement/Reduction	Final print size	Total # of prints

Print surface options: HeavyWeight Matte Paper (standard) Gloss paper Canvas Vinyl Lexan Tyvek Backlit

CURRENT LAMINATION AND MOUNTING LIMITATIONS:

Currently we are only able to mount and laminate up to a width of 36". As long as one deminsion is within 36" we can laminate up to a length of 12' and mount up to a length of 8'.

Lamination: Matte Gloss DisplayFlex

Mounting: FomeCore, 1/4" White Black FomeCore, 1/8" (white only)
 Gatorfoam, 3/16" Natural Black Gatorfoam, 1/2") White Black
 Komatex (PVC), 2mm White Black Komatex, 3mm White Black
 Coroplast 4mm (white only) Coroplast 6mm (white only)
 Polybacker, 10mil (for Lexan & DisplayFlex applications)
 Apply 1/4" velcro edging
 Grommetes

Special trimming instrutions: _____

Packaged for shipping, Ship to: _____

Ship overnight Client FedX shipping # _____ Ship ground UPS

Client Contact: _____ Organization _____ Phone _____

PDF Files: PDF files can be generated for screen, print, or press. Our requirements are for print provided output will be at or below 125% of document layout size. If a file is to be printed above 125% it should be provided as a PDF for press output. This is not a concern if files do not contain bitmap (photo) elements.